This document is the property of Amphenol Corporation and is delivered on the express condition that is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, and that no right is granted to disclose or to use any information in this document.

The marking on thisproduct doesn't contain environmental hazardous materials per Material Specification SS-00259 for Sony GP compliant or per directive 2002/95/EC for RoHS compliant.

REVISIONS				
SYM	ECN No.	DESCRIPTION	DATE	APPROVED
AX1	N2236V	NBO NO: PROPOSAL ONLY	XX/XX/2008	XXX





PCB HOLES





SCHEMATIC DIAGRAM

NO	PART NAME	QTY	MATERIAL	REMARK
7	SHIELDING	1	H62Y t0.3	Sn-PLATED
6	WASHER	6	PBT	
5	HOUSING	1	PBT	
4	OUTER CONTACT	1	H62M t=0.4	Sn-PLATED
3	OUTER CONTACT	1	H62M t=0.4	Sn-PLATED
2	L-TERMINALE	3	H62Y t=0.4	Sn-PLATED
1	S-TERMINALE	3	H62Y t=0.4	Sn-PLATED

SPECIFICATION

1. Rating : DC 30V 0.5A
2. Contact resistance: ≤50mΩ
3. Insulation resistance: >100MΩ (DC250V)
4. Withstand voltage: 250VAC
5. Insertion and extraction force: 3-25N
6. life test: 1,000 cycles

TOLERANCE	APPROVALS	DATE
X.	DRAWN	
X.X ±0.30	DESIGNED Roger Tsai	04/13/2009
X.XX ±0.20	CHECKED Daniel Hsieh	04/13/2009
X.XXX ±0.10	APPROVED Hank Hsu	04/13/2009
ANGULAR ±1°	DWG TYPE CUST DWG	PROJECT CODE OTHER
UNLESS OTHERWISE SPECIFIED		

TITLE: RCA JACK
VERTICAL, DIP TYPE

Amphenol ®
Amphenol Corporation
Amphenol Taiwan Corporation

UNIT mm | SIZE A3 | SCALE NA | SHEET 1 OF 1

PART No. GMSBXXXAXXXEU

DWG No. GMSBXXXAXXXEU | REV. AX1